

## SI Rod end SI70-ES-DURBAL - SI70-ES-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/si70-es-durbal>

### SI70-ES



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2/R5 with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**Rod end body:** surface zinc plated

order number		measurement (mm)							
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4	
SI 70 ES		70	M 56 x 3	49	42,0	160	80,0	98	

type	measurement [mm]			$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h			
SI / SII 70 ES	80	85	200	6	610,0	8,6

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497747
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SI
Weight	8600 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE