

## SI Rod end SI80-ES-2RS-DURBAL - DSI80-ES-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/dsi80-es-2rs-durbal>

### SI80-ES-2RS



female thread;  
lubrication  
required,  
according to  
DIN ISO 12240-4;  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and  
phosphated

Outer ring:  
bearing steel, hardened, ground and  
phosphated

Lubrication:  
lubrication required



order number		measurement (mm)							
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4	
SI 80 ES (-2RS)		80	M 64 x 4	55	47,0	180	95,0	110	

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	W	h	α [°]		
SI / SIL 80 ES (-2RS)	85	100	230	6	750,0	12,0

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497785
Inside diameter	80 mm
Outside diameter	180 mm
Thickness	55 mm
Type	SI
Weight	12000 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE