

SA Rod end SAL12-E-DURBAL - DSAL12-E-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/dsal12-e-durbal>

SAL12-E



male thread: lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 12 E	12	M 12	10	8,0	34

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 12 E	28	17	54	11	24,5	0,085	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497983
Inside diameter	12 mm
Outside diameter	34 mm
Thickness	10 mm
Type	SA
Weight	86 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE