

## SA Rod end SAL15-ES-DURBAL - SAL15-ES-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sal15-es-durbal>

### SAL15-ES



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


**Ball end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
	<b>SAL 15 ES</b>	15	M 14	12	10,0	40

type	measurement [mm]			n	load rating	weight
	l <sub>1</sub> min	l <sub>2</sub>	h	[°]	C <sub>0</sub> [kN]	[kg]
SA / SAL 15 ES	34	20	63	8	36,0	0,140

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498072
Inside diameter	15 mm
Inside diameter	0.591" inch
Outside diameter	40 mm
Outside diameter	1.575" inch
Thickness	12 mm
Thickness	0.472" inch
Type	SA
Weight	140 g
Thread	Left-hand thread
Lubrication	with
Packaging	-
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE