

## SA Rod end SA30-ES-DURBAL - SA30-ES-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sa30-es-durbal>

### SA30-ES



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
SA 30 ES		30	M 30 x 2	22	19,0	73	

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h	n [°]		
SA / SAL 30 ES	65	37	110	6	110,0	0,890

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498355
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	73 mm
Outside diameter	2.874" inch
Thickness	22 mm
Thickness	0.866" inch
Type	SA
Weight	890 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE