

SA Rod end SAL40-ES-2RS-DURBAL - SAL40-ES-2RS-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/sal40-es-2rs-durbal>

SAL40-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 40 ES (-2RS)	40	M 39 x 3	28	23,0	92	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 40 ES (-2RS)	86	46	150		7	180,0	1,800

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498553
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	92 mm
Outside diameter	3.622" inch
Thickness	28 mm
Thickness	1.102" inch
Type	SA
Weight	1800 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE