

SA Rod end SAL70-ES-DURBAL - DSAL70-ES-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/dsal70-es-durbal>

SAL70-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 70 ES	70	M 56 x 4	49	42,0	160	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 70 ES	125	80	235	6	610,0	8,200	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498867
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SA
Weight	8200 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE