

TAPR Rod end GIHN-K-32LO-DURBAL - GIHN-K-32LO-DURBAL


<https://www.123bearing.com/bearing-housing/rod-end/tapr/gihn-k-32lo-durbal>

GIHN-K-32LO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. LO pressed into rod end housing. Sliding combination steel / steel with grease nipple.

* without grease nipple



female thread;
hydraulic rod ends,
according to
DIN 24338

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
phosphated

Outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required

order number	d	d ₁	measurement [mm]	G	d ₂	B	C ₁	C ₂
GIHN-K 32 LO	32	71	M 27 x 2	38,0	66	32	28	22

type	l ₁ min	measurement [mm]	l ₂	l ₃	load rating	weight
		h	l ₂	l ₃	C ₀ [kN]	[kg]
GIHN-K / GIHN-KL 32 LO	37	80	118,5	32	114,0	1,20

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500188
Inside diameter	32 mm
Outside diameter	71 mm
Thickness	28 mm
Type	TAPR
Weight	1200 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE