

TAPR Rod end GIHN-KL-70LO-DURBAL - GIHN-KL-70LO-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/tapr/gihn-kl-70lo-durbal>


GIHN-KL-70LO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. LO pressed into rod end housing. Sliding combination steel / steel with grease nipple.

* without grease nipple

female thread;
hydraulic rod ends,
according to
DIN 24338



Sliding combination:

steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number	d	d ₁	measurement [mm]	G	d ₂	B	C ₁	C ₂
right hand thread								
left hand thread								
GIHN-KL 70 LO	70	155	M 56 x 2	80,0	135	70	57	42

type	l ₁ min	measurement [mm]	l ₂	l ₁	load rating	weight
GIHN-K / GIHN-KL 70 LO	76	160	245,0	70	540,0 (KN)	9,50 (kg)

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500379
Inside diameter	70 mm
Inside diameter	2.756" inch
Outside diameter	155 mm
Outside diameter	6.102" inch
Thickness	57 mm
Thickness	2.244" inch
Type	TAPR
Weight	9500 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE