

TAPR Rod end GIHO-KL-16DO-DURBAL - GIHO-KL-16DO-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/tapr/giho-kl-16do-durbal>

GIHO-KL-16DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
	GIHO-KL 16 DO*	16	20,7	45	M 12 x 1,25	21	45	14	11	13	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 16 DO	48	17	70,5	20	10	28,5	0,22

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500645
Inside diameter	16 mm
Outside diameter	45 mm
Thickness	11 mm
Type	TAPR
Weight	220 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE