

# TAPR Rod end GIHO-KL-20DO-DURBAL - GIHO-KL-20DO-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/tapr/giho-kl-20do-durbal>

## GIHO-KL-20DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-KL 20 DO*		
	20	24,1 55 M 14 x 1,5 25 55 16 13 17

type	measurement [mm]				$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$h_1$	$l_1$	$l_2$	$l_3$			
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500690
Inside diameter	20 mm
Outside diameter	55 mm
Thickness	13 mm
Type	TAPR
Weight	430 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE