

TAPR Rod end GIHO-KL-40DO-DURBAL - GIHO-KL-40DO-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/tapr/giho-kl-40do-durbal>

GIHO-KL-40DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-KL 40 DO		40	45,0	100	M 27 x 2	45	90	28	23	23	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHN-K / GIHN-KL 40 DO	105	37	155,0	45	7	156,0	2,16

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500805
Inside diameter	40 mm
Outside diameter	100 mm
Thickness	23 mm
Type	TAPR
Weight	2160 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE