

TAPR Rod end GIHO-K-50DO-DURBAL - GIHO-K-50DO-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/tapr/giho-k-50do-durbal>

GIHO-K-50DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-K 50 DO		50	56,0	120	M 33 x 2	55	105	35	30	30	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHN-K / GIHN-KL 50 DO	130	46	190,0	58	6	245,0	3,90

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500843
Inside diameter	50 mm
Outside diameter	120 mm
Thickness	30 mm
Type	TAPR
Weight	3900 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE