

TAPR Rod end GIHO-K-60DO-DURBAL - GIHO-K-60DO-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/tapr/giho-k-60do-durbal>

GIHO-K-60DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]		
right hand thread	left hand thread		
GIHO-K 60 DO	60	66,8 160 M 42 x 2	68 134 44 38 38

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	h_1	l_1	l_2	l_3			
GIHN-K / GIHN-KL 60 DO	150	57	230,0	68	6	380,0	7,15

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500898
Inside diameter	60 mm
Outside diameter	160 mm
Thickness	38 mm
Type	TAPR
Weight	7150 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE