

SI Rod end

PF10-00-501-DURBAL - PF10-00-501-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/si/pf10-00-501-durbal>

PF10-00-501

rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields

order number		measurements (mm)									
type	right hand thread	left hand thread	d1	d2	d3	d4	d5	d6	b1	b2	
PF 10 -00 -501			10	15	M 8	13,0	30	13,0		9	

type	measurements (mm)					weight [kg]	calculation factors Y	rotational speed limit nmax [min-1]	basic load rating dyn. C [N]	stat. C0 [N]		
	h	l	l3	r	SW							
PF 10	38	17	14,5	10	13	7,0	0,063	1,90	1,81	1225	2605	985

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507361
Inside diameter	10 mm
Outside diameter	30 mm
Thickness	13 mm
Type	-
Weight	63 g
Thread	-
Lubrication	-
Packaging	-

contact@123bearing.com
(646) 712 9672
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE