

SA Rod end PM05-01-502-DURBAL - PM05-01-502-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/pm05-01-502-durbal>

PM05-01-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight			rotational speed limit			basic load rating	
type	sp/nd/ht/ma	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.		
PM 05 -01	-502	5	M 8 x 1		7.5	19	12	12	8										
measurements [mm]		weight			rotational speed limit			basic load rating											
type	l1	l2	l3	h1	h2	u	z	alpha [°]	weight [kg]	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.			
PM 05	16	13	33.5	1.5	2.5	7.0			0,033	1,51	1,58	1350	1610	480					

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507446
Inside diameter	5 mm
Outside diameter	19 mm
Thickness	12 mm
Type	SA
Weight	33 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE