

## SA Rod end PM06-00-502-DURBAL - PM06-00-502-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/pm06-00-502-durbal>

### PM06-00-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating			
type	specification	d1	d2	d4	d5	d7	b1	b2	Y	Yc	C	C0	
PM 06 -00	-502	6	M 10 x 1	8,5	24	14	14	10					
measurements [mm]		weight		rotational speed limit		basic load rating		dyn.		stat.			
type	l1	l2	l3	h1	h2	u	z	α [°]	(kg)	(min <sup>-1</sup> )	(N)	(N)	
PM 06	42,5	17	64	1,5	2,5	10,5	0,062		1,28	1,34	1300	2445	765

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507477
Inside diameter	6 mm
Outside diameter	24 mm
Thickness	14 mm
Type	SA
Weight	62 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE