

SA Rod end PM10-03-501-DURBAL - PM10-03-501-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/pm10-03-501-durbal>

PM10-03-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	type	
PM 10 -03 -501		10	M 14 x 1,5	12,5	36	19	20	14				
measurements [mm]		weight		rotational speed limit		basic load rating						
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	gamma	
PM 10	26	28	58,5	2,5	2,5	9,5	0,154	1,69	1,77	1100	5120	1905

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507576
Inside diameter	10 mm
Outside diameter	36 mm
Thickness	20 mm
Type	SA
Weight	154 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE