

SA Rod end PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123bearing.com/bearing-housing/rod-end/sa/pm15-02-501-durbal>

PM15-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating	
type	sp. hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	stat. [N]
PM 15 -02	-501	15	M 20 x 1.5	18.5	42	26	20	14							
measurements [mm]		weight		rotational speed limit		basic load rating									
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	stat. [N]
PM 15	36	30	73.5	3.0	2.5	6.5	0.273		2.07	2.17		975	5485	3270	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507651
Inside diameter	15 mm
Outside diameter	42 mm
Thickness	20 mm
Type	SA
Weight	273 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE