


## Drawn cup roller bearing FC-4-K-NADELLA - FC-4-K-NADELLA

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/fc-4-k-nadella>

### Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



FCS, FCL-K + FC-K



Shaft Ø mm	Designation	F <sub>o</sub> mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
4	FC-4-K	4	8	6	0.349	28000	HK0408

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
4	7.984	3.980	4.004	11	4.000	3.985	7.983	7.984	0.001

## PRODUCT FEATURES

Brand	NADELLA
N° Ean13	3616060472502
Inside diameter	4 mm
Outside diameter	8 mm
Thickness	6 mm
Weight	1 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE