

Drawn cup roller bearing FCS-35-NADELLA - FCS-35-NADELLA

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/fcs-35-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F _o mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
35	FCS-35	35	42	20	107.0	6100	HK3512

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Mounting		Max. mm	Min. mm	
35	41.972	34.964	35.009	56	Max. mm	Min. mm	Max. mm	Min. mm	0.048

PRODUCT FEATURES

Brand	NADELLA
N° Ean13	3663952529509
Inside diameter	35 mm
Inside diameter	1.378" inch
Outside diameter	42 mm
Outside diameter	1.654" inch
Thickness	20 mm
Thickness	0.787" inch
Weight	48 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE