


Drawn cup roller bearing SJ7295-SS-RBC - SJ7295-SS-RBC

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/sj7295-ss-rbc>

Precision Ground Heavy Duty Needle Roller Bearings with Seals 



TYPE - SS
Outside seal with optional seal
turned outward to
encourage
bearing # SJ - 25



| BEARING PART NUMBER | Fw Inside Diameter | | | D Outside Diameter | | B Width +.000 - .020 | A Housing Fit Max. | Approx. Weight (Lbs.) | Housing Shoulder Dia. $\pm .004$ | Dynamic Capacity C (Lbs.) | Static Capacity Co (Lbs.) |
|---------------------|--------------------|--------|--------|--------------------|--------|----------------------|--------------------|-----------------------|----------------------------------|---------------------------|---------------------------|
| | Nominal | Min. | Max. | Max. | Min. | | | | | | |
| SJ 7295 SS | 1.618 | 1.6290 | 1.6390 | 2.1475 | 2.1489 | 1.250 | .06 | .458 | 1.1518 | 10,000 | 19,500 |

| Limits Speed (rpm) | Recommended Shaft Diameter | | | | Recommended Housing Bore | | | | BEARING PART NUMBER | | |
|--------------------|----------------------------|--------|-------------------------|--------|--------------------------|--------|------------------|--------|---------------------|--------|------------|
| | ISO H6, use with H7 fit | | ISO H8, use with N7 fit | | Slip Fit ISO H7 | | Press Fit ISO N7 | | | | |
| | Max. | Min. | Max. | Min. | Min. | Max. | Min. | Max. | Min. | Max. | |
| 2,400 | 1.6250 | 1.6244 | 1.6240 | 1.6234 | 2.1475 | 2.1487 | .0026L | 2.1480 | 2.1471 | .0008T | SJ 7295 SS |

All dimensions in inches.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | RBC |
| N° Ean13 | 3663952531588 |
| Inside diameter | 41.275 mm |
| Outside diameter | 55.563 mm |
| Thickness | 31.75 mm |
| Weight | 212 g |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE