

# GE Rod end

## MH-M10-C-DUNLOP - MH-M10-C-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/ge/mh-m10-c-dunlop>

**MALE ROD ENDS** **DUNLOP**



**MH SERIES: MH - MHS - MH SS**

**Description:**  
MH series is our 3-piece unique internationally patented range of male rod ends incorporating a polyurethane bearing race that provides ultra smooth operation. A nitroce surface protected ball with a PTFE lubricant provide superior shock load and extended wear properties, combined with excellent chemical and corrosion resistance. The unique innovative captive body design prevents detachment through excessive axial loads. For optimum performance, ensure that the rod end is mounted with the moulded lettering facing away from the direction of pull.

**Material Specifications:**  
Housing: Steel 230M07PB zinc plated and clear trivalent passivate. Race: Polyurethane. Ball: 230M07PB nitroce finish. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303C. Lubricant: UniFor oil.

**Features:**  
Metric & imperial sizes  
Ultra low friction  
High shock loads  
Extended wear life  
No maintenance  
Skidged option

**Possible Applications:**  
Light to medium  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control  
Safety features

**Temperature Range:**  
-40°C to + 80°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Steel 230M07PB zinc Plated and Clear Trivalent Passivate. **Ball:** Steel 230M07PB - Nitroce Surface Protection

**Race:** Polyurethane **Lubricant:** UniFor Oil

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MH-M10C		10	M10x1.25	14	10.50	28	48	28	12.85	21,078

**MALE ROD ENDS**

**DUNLOP**

**MH SERIES: MH - MHS - MH SS**

**Description:**  
MH series is our 3-piece unique internationally patented range of male rod ends incorporating a polyurethane bearing race that provides ultra smooth operation. A nitroce surface protected ball with a PTFE lubricant provide superior shock load and extended wear properties, combined with excellent chemical and corrosion resistance. The unique innovative captive body design prevents detachment through excessive axial loads. For optimum performance, ensure that the rod end is mounted with the moulded lettering facing away from the direction of pull.

**Material Specifications:**  
Housing: Steel 230M07PB zinc plated and clear trivalent passivate. Race: Polyurethane. Ball: 230M07PB nitroce finish. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303C. Lubricant: UniFor oil.

**Features:**  
Metric & imperial sizes  
Ultra low friction  
High shock loads  
Extended wear life  
No maintenance  
Skidged option

**Possible Applications:**  
Light to medium  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control  
Safety features

**Temperature Range:**  
-40°C to + 80°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Steel 230M07PB zinc Plated and Clear Trivalent Passivate. **Ball:** Steel 230M07PB - Nitroce Surface Protection

**Race:** Polyurethane **Lubricant:** UniFor Oil

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MH-M10C		10	M10x1.25	14	10.50	28	48	28	12.85	21,078

## PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060473240
Inside diameter	10 mm
Outside diameter	28 mm
Thickness	10.5 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE