

## Deep groove ball bearing single row 3014-SC-NICE - 3014-SC-NICE

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/3014-sc-nice>

**3000 Series® Semi-Ground Radial Bearings** **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	
3014™	SC					
					<b>BORE</b> <b>d</b> (in) (mm)	<b>O.D.</b> <b>D</b> (in) (mm)
					+0.005 +0.13 -0.000 -0.05	+0.000 +0.00 -0.005 -0.015
					0.3750 9.525	1.1250 28.575

WIDTH <b>B</b> (in) (mm)	BASIC LOAD RATINGS		WEIGHT <b>W</b> (lbs) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC <b>C</b> (lbs) (N)	STATIC <b>Co</b> (lbs) (N)		<b>d<sub>a</sub> min</b> (in) (mm)	<b>D<sub>a</sub> max</b> (in) (mm)	<b>r max</b> (in) (mm)
0.3750 9.525	600 2670	475 2114	0.06 0.03	0.585 15.11	1.014 25.76	0.025 0.64

Ⓢ Weights given are for greased and sealed versions  
Ⓢ 3038 and larger +0.000/-0.005 (+0.000/-0.15)

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558332
Inside diameter	9.525 mm
Outside diameter	28.575 mm
Thickness	9.525 mm
Weight	30 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE