

Deep groove ball bearing single row 3041-SS-NICE - 3041-SS-NICE

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/3041-ss-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3041™				SS		+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 ⓐ -0.013
						1.0000 25.400	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.9625 14.288	1480 6586	1350 6008	0.26 0.12	1.197 30.40	1.760 44.70	0.035 0.89

ⓐ Weights given are for greased and sealed versions
ⓑ 3038 and larger +0.0005/-0.0005 (+0.001/-0.013)

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558912
Inside diameter	25.4 mm
Outside diameter	50.8 mm
Thickness	14.288 mm
Weight	120 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE