


Deep groove ball bearing single row 410-30V-NICE - 410-30V-NICE

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/410-30v-nice>

400 Series® Single Row Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
410™	30V	0.625 15.88 +0.0002 -0.0004	3.375 85.72 +0.0050 -0.0050	0.470 11.94 +0.0100 -0.0100	0.500 12.70 Reference	16	3/16 4.75

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
	(N)	(N)	(N)	(N)	(N)	(N)
0.10	375	261	180	145	101	71
0.05	1989	1181	801	645	449	316

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560113
Inside diameter	15.88 mm
Outside diameter	34.93 mm
Thickness	11.94 mm
2nd Thickness	12.7 mm
Weight	50 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE