


Deep groove ball bearing single row 416-41V-NICE - 416-41V-NICE

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/416-41v-nice>

400 Series® Single Row Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
416™	41V	1.000 25.40±0.000	2.000 50.80±0.000	0.572 14.53±0.010	0.625 15.88±0.010	17	1/4 6.35

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
	(N)	(N)	(N)	(N)	(N)	(N)
0.30	757	525	362	293	204	142
0.14	3389	2338	1611	1304	928	632

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560168
Inside diameter	25.4 mm
Inside diameter	1" inch
Outside diameter	50.8 mm
Outside diameter	2" inch
Thickness	14.53 mm
Thickness	0.572" inch
2nd Thickness	15.88 mm
2nd Thickness	5/8" inch
Weight	140 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE