


Deep groove ball bearing single row 400-47V-NICE - 400-47V-NICE

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/400-47v-nice>

400 Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm) +0.000/-0.0005	B O.D. (in) (mm) +0.0005/0.000	C WIDTH (in) (mm) +0.010/-0.010	D WIDTH (in) (mm) Reference	No.	Size (mm)
400™	47V	1.250 31.75	2.625 66.68	0.687 17.45	0.687 17.45	23	1/4 6.35

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.75 0.34	1020 4539	710 3160	490 2181	395 1758	275 1224	193 869

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560175
Inside diameter	31.75 mm
Outside diameter	66.68 mm
Thickness	17.45 mm
Weight	340 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE