

## Deep groove ball bearing single row 5281-V-NICE - 5281-V-NICE

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/5281-v-nice>

**5000** Series® Single Row Unground Flanged Radial Bearings (con't) **NICE™**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
		+0.005/-0.000 +13/-00	+0.005/+0.000 +18/-00	+0.010/-0.010 +25/-25				+0.010/-0.010 +25/-25
5281™	V	0.500 12.70	1.539 40.08	0.515 13.08	0.140 3.56	1.887 42.85	0.234 5.94	0.809 15.47

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (lbs) (%)	100 (lbs) (%)	200 (lbs) (%)	300 (lbs) (%)	600 (lbs) (%)	1200 (lbs) (%)	
12	1/4 6.35	0.22 0.10	535 2381	367 1633	258 1148	206 917	144 641	100 445

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560298
Inside diameter	12.7 mm
Outside diameter	40.08 mm
2nd Outside diameter	42.85 mm
Thickness	13.08 mm
2nd Thickness	15.47 mm
Weight	100 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE