

TSM Rod end MX-05-4-DUNLOP - MX-05-4-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/tsm/mx-05-4-dunlop>

MALE ROD ENDS **DUNLOP**

DUNLOP
MALE ROD ENDS

MX SERIES

Description:
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: 817M 40, heat treated to 85/90 tons/m² tensile, Phosphated all over.
Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged 817M40, Heat Treated to 85/90 tons/m² tensile and Phosphated all over. **Balls:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MX-05-R	MX-05-L	20.624	9.525	20.624	20.624	6.35	1.625	1.625	3/16 UNF	22	11770

Interchange table

Dunlop	Rose	NMB
MX-M (Metric)	RJ-M	RJ-M
MX (Imperial)	RJ-I	RJ-I

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.
'0' in part number denotes grease nipple is fitted.

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060550644
Inside diameter	6.35 mm
Outside diameter	20.624 mm
Thickness	9.525 mm
Type	TSM
Thread	Right-hand thread
Lubrication	with
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE