

## SI Rod end FX-M20-CG-DUNLOP - FX-M20-CG-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/si/fx-m20-cg-dunlop>

FEMALE ROD ENDS DUNLOP



**FX SERIES**

**Description:**  
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: S17M 4J, heat treated to 80/90 tons/in<sup>2</sup> tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available  
Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Forged S17M4J, heat treated to 80/90 tons/in<sup>2</sup> tensile all over, Phosphate all over.

**Ball:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	D	F	A	J	M	X	Static Load Rating (Newtons) Radial	
FXL-M20CG		20	22.2	20.6	25.4	54.0	79.2	44.0	28.5	M20 x 1.50	16	110810

**Interchange table**

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

### PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060555090
Inside diameter	20 mm
Outside diameter	22.2 mm
Thickness	20.6 mm
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE