

SI Rod end FXL-M10-DUNLOP - FXL-M10-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/si/fxl-m10-dunlop>

FEMALE ROD ENDS



FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 4J, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M4J, heat treated to 80/90 tons/in² tensile and phosphated all over. **Ball:** Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newtons) Radial
FXL-M10	10	14.2	12.2	14.2	31.0	41.2	21.0	15.2	M10 x 1.50	22		27460

Interchange table

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060555151
Inside diameter	10 mm
Inside diameter	0.394" inch
Outside diameter	14.02 mm
Outside diameter	0.552" inch
Thickness	12.2 mm
Thickness	0.48" inch
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE