

# SI Rod end FSLX-12-10-DUNLOP - FSLX-12-10-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/si/fslx-12-10-dunlop>

**FEMALE ROD ENDS**



**FSLX SERIES**

**Description:**  
FSLX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate  
Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C  
Liner: High Strength PTFE Composite

**Features:**  
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

**Temperature Range:**  
-200°C to +240°C

**Possible Applications:**  
Motorsport and heavy industrial mechanical applications.

**Specification:**  
ELV & RoHS compliant applications.

**Temp Range:** -200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-12-10		5/8	3/4 UNF	0.875	0.687	2.000	2.875	1.750	1.000	9300

**Interchange table**

Dunlop	Aurora	Fluro
FSLX-M (Metric)	AW-M-T and AD-M-T	GUSW
FSLX (Imperial)	AW-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556226
Inside diameter	15.875 mm
Outside diameter	50.8 mm
Thickness	22.225 mm
Type	SI
Thread	Left-hand thread
Lubrication	NA
Static load	93.5 kN
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE