



SI Rod end AL-SA-090-LH-DUNLOP - AL-SA-090-LH-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/si/al-sa-090-lh-dunlop>

FEMALE ROD ENDS DUNLOP

Housing: Aluminum A6061, Black Anodized

AL SERIES

Description:
AL-Series is our 3-piece aluminum light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminum A6061, black anodized. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features Metric bore & thread sizes Low friction Self-lubricating Good wear resistance Excellent moisture resistance No maintenance Light weight	Possible Applications Light industrial/mechanical applications Weight restricted applications Linear movement sensors	Temperature Range -30°C to +170°C Specification ELV & RoHS compliant
--	---	---

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-090LH		9	M4x0.75	6	4.50	12	19.5	6.0	5.2	6.0	3,040

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556561
Inside diameter	3 mm
Outside diameter	6 mm
Thickness	4.5 mm
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE