


SI Rod end

DB-SA-195-DUNLOP - DB-SA-195-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/si/db-sa-195-dunlop>

MALE ROD ENDS **DUNLOP**



DB SERIES: DBM - DBI

Description:
DB-Series is our 3-piece 'dog bone' range of rod ends primarily based on our MP-Series with regards to function and structure. A wide range of preset centre distances are available. Suitable for light to medium industrial/mechanical load applications requiring low friction, with good wear resistance and available in both metric and imperial bore sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Steel Z30M07PB zinc plated and clear trivalent passivate.
Race: GR-Nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric & imperial thread & bore sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance

Possible Applications:
Light to medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles

Temperature Range:
-30°C to +70°C

Specifications:
ELV & RoHS compliant

Housing: Steel Z30M07PB, Zinc Plated and Clear Trivalent Passivate

Race: GR-Nylon, LV-3H

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No.	Bore Size	C	W	H	D	Ø	Liner	Static Load Rating (Newtons) Radial
DB-SA-195	3/8	70.0	0.500	0.406	1.800	0.516	GR-NYLON	18,900

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556882
Inside diameter	9.52 mm
Inside diameter	0.375" inch
Outside diameter	70 mm
Outside diameter	2.756" inch
Thickness	0.5 mm
Thickness	0.02" inch
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE