

SI Rod end

DB-SA-173-DUNLOP - DB-SA-173-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/si/db-sa-173-dunlop>

MALE ROD ENDS

DB SERIES: DBM - DBI

Description:
DB-Series is our 3-piece 'dog bone' range of rod ends primarily based on our MP-Series with regards to function and structure. A wide range of preset centre distances are available. Suitable for light to medium industrial/mechanical load applications requiring low friction, with good wear resistance and available in both metric and imperial bore sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Steel 230M07PB zinc plated and clear trivalent passivate.
Race: GR-Nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric & imperial thread & bore sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance

Possible Applications:
Light to medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles

Temperature Range:
-30°C to +170°C

Specifications:
ELV & RoHS compliant

Housing:	Steel 230M07PB, Zinc Plated and Clear Trivalent Passivate	Race:	GR-Nylon, LV-3H
		Ball:	Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No.	Bore Size	C	W	H	D	O	Liner	Static Load Rating (Newtons) Radial
DB-SA-173	8	75.0	12	9.9	22	10.4	GR-NYLON	12,775

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060557001
Inside diameter	8 mm
Outside diameter	75 mm
Thickness	12 mm
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE