


# SI Rod end DB-SA-200-DUNLOP - DB-SA-200-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/si/db-sa-200-dunlop>

**MALE ROD ENDS** **DUNLOP**



**DB SERIES: DBM - DBI**

**Description:**  
DB-Series is our 3-piece 'dog bone' range of rod ends primarily based on our MP-Series with regards to function and structure. A wide range of preset centre distances are available. Suitable for light to medium industrial/mechanical load applications requiring low friction, with good wear resistance and available in both metric and imperial bore sizes. They have excellent moisture resistance and require no maintenance.

**Material Specifications:**  
Housing: Steel 230M07PB zinc plated and clear trivalent passivate.  
Race: GR-Nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

**Features:**  
Metric & imperial thread & bore sizes  
Low friction  
Self-lubricating  
Good wear resistance  
Excellent moisture resistance  
No maintenance

**Possible Applications:**  
Light to medium/heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles

**Temperature Range:**  
-30°C to +170°C

**Specifications:**  
ELV & RoHS compliant

**Housing:** Steel 230M07PB, Zinc Plated and Clear Trivalent Passivate

**Race:** GR-Nylon, LV-3H

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No.	Bore Size	C	W	H	D	O	Liner	Static Load Rating (Newtons) Radial
DB-SA-200	10	40.0	14	18.5	26	12.9	SINTERED BRONZE	16,760

## PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060557056
Inside diameter	10 mm
Outside diameter	60 mm
Thickness	14 mm
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE