

## GE Rod end GE60-UK-DUNLOP - GE60-UK-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/ge/ge60-uk-dunlop>

SPHERICAL BEARINGS



**SPHERICAL BEARINGS**

**GE UK SERIES**

**Description:**  
GE-UK-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.  
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.  
Seals: Polyurethane.

**Features**  
Metric bore sizes  
Low friction  
High shock loads  
Extended wear life  
No maintenance


**Possible Applications**  
Medium/heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control.

**Temperature Range**  
-200°C to +240°C

**Specification**  
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened      Balls: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated  
Liner: High Temperature PTFE Composite

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE60UK		60	44	36	90	495,000



### PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060558602
Inside diameter	60 mm
Outside diameter	90 mm
Thickness	44 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE