

# SA Rod end FSLX-M12-10-C-DUNLOP - FSLX-M12-10-C-DUNLOP

<https://www.123bearing.com/bearing-housing/rod-end/sa/fslx-m12-10-c-dunlop>

**FEMALE ROD ENDS**



**DUNLOP FSX SERIES**

**Description:**  
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 708M40, Heat Treated, Zinc plated and clear trivalent passivate.  
Inner Ring: Steel 670M20, zinc plated and clear trivalent passivate and stainless steel 304C. Liner High strength PTFE bronze mesh composite.  
Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C.

**Features:**  
Metric & imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

**Temperature Range:**  
-200°C to + 240°C

**Possible Applications:**  
Motorsport and heavy industrial mechanical applications.

**Specifications:**  
ELV & RoHS compliant

**Notes:**  
Housing: Steel 708M40, Heat Treated, Zinc plated and Clear Trivalent Passivate  
Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate  
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated  
Liner: High Strength PTFE Composite  
Temp Range: -200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-M12-10C		10	M12x1.25	16	12.00	32	50	22	19	42000

**Interchange table**

Dunlop	Aurora	Fluro
FSX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060558862
Inside diameter	10 mm
Outside diameter	32 mm
Thickness	16 mm
Type	SA
Thread	Left-hand thread
Lubrication	NA
Static load	42 kN
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE