

Drawn cup roller bearing BA268-Z-IKO - BA268-Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/ba268-z-iko>



| Boundary dimensions mm(inch) | | | Standard mounting dimensions mm | | | | Basic dynamic load rating | Basic static load rating | Allowable rotational speed(I) | Assembled inner ring |
|------------------------------|------------|--------------|---------------------------------|-------|------|------|---------------------------|--------------------------|-------------------------------|----------------------|
| F_w | D | C | d | h_6 | B | C | C_0 | | | |
| | | | Max. | Min. | Max. | Min. | R | R | rpm | |
| 41.275 (1 1/4) | 50.800 (2) | 12.700 (500) | 2.8 | | | | 13700 | 19800 | 8000 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060601483 |
| Inside diameter | 41.275 mm |
| Outside diameter | 50.8 mm |
| Thickness | 12.7 mm |
| Limiting speed | 8000 rpm |
| Dynamic load | 13.7 kN |
| Static load | 19.8 kN |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE