

## Drawn cup roller bearing BA57-Z-IKO - BA57-Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/ba57-z-iko>



| Boundary dimensions mm(inch) |               |               | Standard mounting dimensions mm |       |        |        | Basic dynamic load rating | Basic static load rating | Allowable rotational speed | Assembled inner ring |
|------------------------------|---------------|---------------|---------------------------------|-------|--------|--------|---------------------------|--------------------------|----------------------------|----------------------|
| $F_w$                        | D             | C             | $d_1$                           | $d_2$ | $d_3$  | $d_4$  | C                         | C <sub>10</sub>          | rpm                        |                      |
| 7,938 (-0,16)                | 12,700 (-0,2) | 11,13(-0,438) | 7,938                           | 7,938 | 12,710 | 12,692 | 3310                      | 3220                     | 45000                      | -                    |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | IKO           |
| N° Ean13         | 3616060601735 |
| Inside diameter  | 7.938 mm      |
| Inside diameter  | 5/16" inch    |
| Outside diameter | 12.7 mm       |
| Outside diameter | 1/2" inch     |
| Thickness        | 11.13 mm      |
| Thickness        | 0.438" inch   |
| Limiting speed   | 45000 rpm     |
| Dynamic load     | 3.31 kN       |
| Static load      | 3.22 kN       |
| Packaging        | 1             |

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE