

Wave spring round wire
WSRW-136.53-6-2.79 - WSRW-136.53-6-2.79

<https://www.123bearing.com/accessories/washer/wave-spring/wsrw-136.53-6-2.79>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/-15 % Newton)
DB = Bearing's outside diameter
Dh = Free fit in hole diameter
Dr = Free fit over hole diameter
N/Wx = Number of waves
PF = Load at flat (approx.)
d = Wire diameter



Wave Springs - Round Wire

Part Number	Wx	Lo (mm)	L1 (mm)	Dr (mm)	Dh (mm)	d (mm)	P1 (N)
RW-0537	6	6.22	4.75	127.94	136.53	2.79	1869

PRODUCT FEATURES

Brand	GEN
Number of corrugations	6
Clearance height	6.22 mm
Packaging	1
Loaded height	4.75
Play on shaft diameter	127.94 mm
Operates in a diameter housing	136.53 mm
Wire diameter	2.79 mm

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE