

**Wave spring round wire**  
**WSRW-152.40-6-3 - WSRW-152.40-6-3**

<https://www.123bearing.com/accessories/washer/wave-spring/wsrw-152.40-6-3>

Do = Outside diameter (max) (mm)  
Di = Inside diameter (min) (mm)  
t = Thickness (mm)  
H = Free height approx.  
H1 = Load at height  
L1 = Load at L1 (+/-15 % Newton)  
DB= Bearing's outside diameter  
Dh = Free fit in hole diameter  
Dr = Free fit over hole diameter  
N/Wx= Number of waves  
Pf=Load at flat (approx.)  
d= Wire diameter



Wave Springs - Round Wire

Part Number	Wx	Lo (mm)	L1 (mm)	Dr (mm)	Dh (mm)	d (mm)	P1 (N)
RW-0600	6	6,81	5,08	143,36	152,40	3,00	2092

**PRODUCT FEATURES**

Brand	GEN
Number of corrugations	6
Clearance height	6.81 mm
Packaging	1
Loaded height	5.08
Play on shaft diameter	143.36 mm
Operates in a diameter housing	152.4 mm
Wire diameter	3 mm

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE