

## Drawn cup roller bearing J-2416-JTEKT - J-2416-KOYO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/j-2416-koyo>

Boundary dimensions



| Bearing No. | Boundary dimensions(mm) |        |      |        | Basic load ratings(kN) |       | Fatigue load limit(kN) |             | Limiting speeds(min-1) |  |
|-------------|-------------------------|--------|------|--------|------------------------|-------|------------------------|-------------|------------------------|--|
|             | Fw                      | D      | C    | Y(max) | Cr                     | COr   | Cu                     | Grease lub. | Oil lub.               |  |
| J-2416      | 38,1                    | 47,625 | 25,4 | 1,27   | 39,32                  | 66,72 | 10,4                   | 5600        | 8600                   |  |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3616060630377 |
| Inside diameter  | 38.1 mm       |
| Outside diameter | 47.625 mm     |
| Thickness        | 25.4 mm       |
| Limiting speed   | 5600 rpm      |
| Dynamic load     | 39.32 kN      |
| Static load      | 66.72 kN      |
| Packaging        | 1             |

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE