

Deep groove ball bearing single row 7315-BECBM-SKF - 7315-BECBM-SKF

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/7315-becbm-skf>

Dimensions d'encadrement		Charges de base		Vitesses de base		Désignation
d	D	B	C	C ₀	Vitesse de référence	Vitesse limite
75	160	37	132	104	5300	5300
mm			kN		tr/min	
<p>Technical drawing showing three views of the bearing: front view, side view, and cross-section. Dimensions include: D=160, D₁=138.7, D₂=91.3, d₁=108.3, d=75, B=37, r_{1,2} max 1.1, r_{1,2} min 0.5, r_{1,2} max 2.1, r_{1,2} min 1.1, D_{max} 148, D_{max} 153, r_{max} 0.4, r_{max} 0.7, r_{max} 1, r_{max} 2. Coefficients de calcul: i₀ 0.5, i₁ 1.8, i₂ 1.14, i₃ 0.35, Y 0.57, Y₀ 0.26.</p>						
* Roulement SKF Explorer						
7315 BECBM *						

PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577150882
Inside diameter	75 mm
Sealing	Non-tight
Cage	Machined metal
Contact angle	40 °
Outside diameter	160 mm
Thickness	37 mm
Limiting speed	6700 rpm
Weight	3200 g
Dynamic load	132 kN
Static load	104 kN
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE