


Tapered roller bearing NN3014-K-NTN - NN3014-K-NTN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/nn3014-k-ntn>



Double Row Cylindrical Roller Bearing w/ Tapered Bore - Type NK - Dimensions

Technical Specifications		Operational Specifications	
Type	Cylindrical Roller Bearing		2.7558 in 70.000 mm
Bore Type	Tapered		4.3307 in 110.000 mm
Material	Hardened Alloy Steel		
Cage Material	High Strength, 2 piece, hardened steel	B	1.1811 in 30.000 mm
Limiting Speed - Oil	6900 RPM	C	1.1811 in 30.000 mm
Limiting Speed - Grease	5800 RPM	Ew	3.9370 in 100.000 mm
Taper	1:12	r	0.0433 in 1.100 mm
Precision	ABEC 3		
Configuration	Open	da min	3.0118 in 76.500 mm
Oil Hole	with Oil Hole	db min	3.1102 in 79.000 mm
Radial Internal Clearance	CN	Da max	3.9764 in 101.000 mm
Static Load Rating	32000 lbf 143200 N 143.00 kN	Db min	3.9764 in 101.000 mm
Dynamic Load Rating	31200 lbf 140000 N 140.00 kN	Db max	4.0748 in 103.500 mm
Enclosure	Open	rsa max	0.0394 in 1.000 mm
Operating Temperature Range	-40 to 250 °F -40 to 120 °C		

PRODUCT FEATURES

Brand	NTN
N° Ean13	3616060804792
Inside diameter	70 mm
Outside diameter	110 mm
Thickness	30 mm
Dynamic load	94.5 kN
Static load	143 kN
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE