

## Gasket sealer

### MR-5922-200ML-LOCTITE - MR-5922-200ML-LOCTITE

<https://www.123bearing.com/lubricant-adhesive/adhesive/gasketsealer/mr-5922-200ml-loctite>

<b>TITRE</b>	Résine
<b>DESCRIPTION</b>	Pâte d'étanchéité souple (ex FAG n°2)
<b>NOM</b>	LOCTITE MR 5922
<b>CONDITIONNEMENT</b>	Tube 200 ml
<b>COMMENTAIRE</b>	
<b>APPROBATION*</b>	

#### Description

LOCTITE® MR 5922 is a black, viscous, solvent-based, slow drying, flexible setting paste that changes to a pliable, non-hardening film through solvent evaporation. It is based on resin, isopropanol and fillers. It seals flanges, fittings, connections and flexible assemblies against leakage. It increases the reliability of gasket seals and it can be used for the repair of damaged pre-cut gaskets.

#### Avantages

Extends gasket life  
Prevents leaks  
Slow drying  
Flexible setting  
Specifically designed to improve the sealing performance of pre-formed gaskets made of cork, metal, plastic, rubber, etc. in non-rigid assemblies  
Increases the reliability of gasket seals

#### Caractéristiques

Flexible sealant paste that changes to a pliable, non-hardening film through solvent evaporation which seals flanges, fittings, connections, etc.

## PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	5010266188645
Weight	341 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE