

Gasket sealer

6482-50ML-LOCTITE - 6482-50ML-LOCTITE

<https://www.123bearing.com/lubricant-adhesive/adhesive/gasketsealer/6482-50ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Scelroulement
NOM	LOCTITE 6482
CONDITIONNEMENT	F1 50 ml
APPROBATION*	PMUC

Description

LOCTITE® 6482 is a green, low-viscosity, urethane methacrylate, acrylic, retaining compound which has a low halogen and sulphur content and was especially developed for use in the nuclear industry. The product is for bonding cylindrical fitting parts, particularly where strength at elevated temperatures is required. Applications include holding gears and sprockets on to gearbox shafts, and rotors on electric motor shafts. Suits sensitive metals such as titanium.

Avantages

Ideal for retaining cylindrical parts
 Offers strength at elevated temperatures
 Prevents loosening and leakage from shock and vibration
 Low halogen and sulfur content
 Suits sensitive metals such as titanium
 Positive fluorescence under UV light

Caractéristiques

Acrylic green retaining compound for bonding cylindrical parts that need to withstand elevated temperatures. It has a low halogene and sulphur content for use in nuclear industry

PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	3616060813787
Weight	89 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE