

## Glue

### EA-9489-400ML-LOCTITE - EA-9489-400ML-LOCTITE

<https://www.123bearing.com/lubricant-adhesive/lubricant/glue/ea-9489-400ml-loctite>

TITRE	Epoxy
DESCRIPTION	Epoxy bi-component gls, couple ratio 1/1, multi-stages
NOM	LOCTITE EA 9489
CONDITIONNEMENT	Ca 2x 400 ml
DANGEROUS GOODS	Yes
COMMENTAIRE	
APPROBATION	

#### Description

LOCTITE® EA 9489 is a 2-part, tough, medium viscosity, industrial grade epoxy adhesive in a 50 ml dual cartridge. Once mixed, the epoxy cures at room temperature to form a flexible grey bondline with medium work life. It can be used for repairing strain gauges, sealing seams on fiberglass components, repairing printed circuit boards, bonding stainless steel inserts and rubber hose to metal tubing.

#### Avantages

Excellent resistance to shock and impact.  
Two-part epoxy is resistant to a wide range of chemicals and solvents and acts as an excellent electrical insulator.  
Suitable for low-stress, high-impact bonding applications of dissimilar materials.

#### Caractéristiques

2-part, tough, medium viscosity, industrial grade epoxy adhesive in a 50 ml dual cartridge.



## PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	3616060815859
Type	COLLAGE RIGIDE EPOXY ACRYLIQUE
Packaging	1
Use	Epoxy

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE