

Housed bearing 2 bolts P2BC-40M-CPSS-DFH-SKF - P2BC-40M-CPSS-DFH-SKF

<https://www.123bearing.com/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/p2bc-40m-cpss-dfh-skf>

Données de calcul	
Charge dynamique de base	C 24.7 kN
Charge statique de base	C ₀ 19 kN
Limite de fatigue	P ₀ 0.8 kN
Compliance with standard	Not standardized
Matériau	Compatible for the SKF Food Line
Sealing solution	Gutter seals
Dimensions	
d	40 mm
A	44 mm
A ₁	44 mm
A ₂	79.9 mm
B	40.7 mm
B ₁	10 mm
B ₂	38.3 mm
H ₁	49.2 mm
H ₂	20 mm
J	137 mm
J	max. 140 mm
J	min. 134 mm
L	179 mm
W	17 mm
N ₁	14 mm
N ₂	30.2 mm
Plots de centrage	
G	12 mm
G	0.6 in
Calculation data	
Limiting speed with shaft tolerance H6	900 v/min

PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577859327
Shaft diameter	40 mm
No. of fasteners	2
Tightening	Eccentric locking ring
Mounting center distance	137 mm
Material	FOOD-GRADE POLYPROPYLENE
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE